

Speaker Type: Component Widerange
 Nominal Diameter: 2.5"/65 mm
 Nominal Impedance (Znom): 4 Ohms
 Continuous Power Handling: 60 W
 Peak Power Handling: 120 W
 Rec. Amplifier Power: 20 - 100W (RMS)

PARAMETERS

Voice Coil Resistance (Re): 3.7 Ohms
 Voice Coil Diameter: 20 mm
 Free Air Resonance (Fs): 143.5 Hz
 Reference Efficiency (no): 0,109 %
 Sensitivity: 83 dB @ 1W/1m
 86 dB @ 2.83V/1m
 Electrical "Q" (Qes): 1.286
 Mechanical "Q" (Qms): 3.428
 Total Speaker "Q" (Qts): 0.935
 Equivalent Compliance (Vas): 0.492 lt
 Moving Mass (Mms): 1.65 g
 Mech. Compliance (Cms): 0.742 mm/N
 Magnetic Strength (BL): 2.08 N/A
 Effective Piston Area (Sd): 21.65 sq. cm
 One-Way Linear Excursion (Xmax): 3 mm

DESIGN BANDWIDTH

With 48 dB/oct. HP filters: 200 Hz - 22 KHz
 With 24 dB/oct. HP filters: 240 Hz - 22 KHz
 With 12 dB/oct. HP filters: 280 Hz - 22 KHz

