

Speaker Type: Component Coaxial
 Nominal Diameter: 6.5"/165 mm
 Nominal Impedance (Znom): 4 Ohms
 Continuous Power Handling: 80 W
 Peak Power Handling: 160 W
 Sensitivity: 88.5 dB @ 1W/1m
 91.5 dB @ 2.83V/1m
 Rec. Amplifier Power: 20 - 140W (RMS)

TWEETER PARAMETERS

Voice Coil Resistance (Re): 3.62 Ohms
 Free Air Resonance (Fs): 1900 Hz
 Electrical "Q" (Qes): 3.805
 Mechanical "Q" (Qms): 2.219
 Total Speaker "Q" (Qts): 1.402

WOOFER PARAMETERS

Voice Coil Resistance (Re): 3.11 Ohms
 Free Air Resonance (Fs): 64.98 Hz
 Reference Efficiency (no): 0,446 %
 Electrical "Q" (Qes): 0.766
 Mechanical "Q" (Qms): 3.026
 Total Speaker "Q" (Qts): 0.611
 Equivalent Compliance (Vas): 13.93 lt
 Moving Mass (Mms): 11.63 g
 Mech. Compliance (Cms): 0.516 mm/N
 Magnetic Strength (BL): 4.39 N/A
 Effective Piston Area (Sd): 132.7 sq. cm
 One-Way Linear Excursion (Xmax): 3.25 mm

