

Speaker Type: Component Mid-Woofer  
 Nominal Diameter: 6.5"/165 mm  
 Nominal Impedance (Znom): 4 Ohms  
 Continuous Power Handling: 150 W  
 Peak Power Handling: 300 W  
 Rec. Amplifier Power: 60 - 225W (RMS)

**PARAMETERS**

Voice Coil Resistance (Re): 2.91 Ohms  
 Voice Coil Diameter: 25.5 mm  
 Free Air Resonance (Fs): 57.3 Hz  
 Reference Efficiency (no): 0,36 %  
 Sensitivity: 89.5 dB @ 1W/1m  
 92.5 dB @ 2.83V/1m  
 Electrical "Q" (Qes): 0.625  
 Mechanical "Q" (Qms): 4.403  
 Total Speaker "Q" (Qts): 0.547  
 Equivalent Compliance (Vas): 12.55 lt  
 Moving Mass (Mms): 15.3 g  
 Mech. Compliance (Cms): 0.504 mm/N  
 Magnetic Strength (BL): 5.065 N/A  
 Effective Piston Area (Sd): 132.73 sq. cm  
 One-Way Linear Excursion (Xmax): 4.5 mm

**DESIGN BANDWIDTH**

With 48 dB/oct. HP filters: 60 Hz - 6 KHz  
 With 24 dB/oct. HP filters: 70 Hz - 6 KHz  
 With 12 dB/oct. HP filters: 80 Hz - 6 KHz

