

Tweeter Type: Silk Dome
 Nominal Diameter: 0.8"/20 mm
 Woofer Type: Paper Cone
 Nominal Diameter: 6.5"/165 mm
 Nominal Impedance (Znom): 4 Ohms
 Continuous Power Handling: 90 W
 Peak Power Handling: 180 W
 Frequency Response: 50 - 20000 Hz
 Sensitivity: 88.0 dB @ 1W/1m
 91.0 dB @ 2.83V/1m

*Cont. and Peak Power @ High-Pass 80Hz - 12dB/Oct.

TWEETER PARAMETERS

Magnet: N-35 Neodymium
 VC Diameter: 20.4 mm
 DC Resistance (Re): 2.4 Ohms

WOOFER PARAMETERS

Magnet: Y-25 Ferrite
 VC Diameter: 25.5 mm
 DC Resistance (Re): 3.3 Ohms
 Mech. Compliance (Cms): 0.44 m/N
 Mechanical "Q" (Qms): 5.29
 Electrical "Q" (Qes): 1.22
 Total Speaker "Q" (Qts): 0.99
 Moving Mass (Mms): 12.2 g
 Equivalent Compliance (Vas): 11.2 lt
 Free Air Resonance (Fs): 68.5 Hz

